

AIR QUALITY
MANAGEMENT DISTRICT

**THESE SUGGESTED FORMS MAY BE USED
TO COMPLY WITH THE RECORDKEEPING
REQUIREMENTS OF RULE 451**
(Surface Coating of Miscellaneous Metal Parts & Products)

- Form 451A List of Currently Used Materials
- Form 451B Monthly Usage and Emissions Record
- Form 451B Sup Quarterly Emissions Summary
- Form 451C Monthly Usage Record for Low Usage Exemption
- Form 451D Daily Usage Record of Non-Compliant Materials
- Form 451E Annual Report for Low Usage Exemption

YOU MAY REPRODUCE THESE FORMS AS NEEDED.

**DEFINITIONS OF MATERIALS USED IN SURFACE COATING
OF MISCELLANEOUS METAL PARTS AND PRODUCTS**

MATERIAL TYPE	DEFINITION
Aluminum Coating for Window Frames and Door Frames	A coating which is applied in a shop environment and is used to protect prefabricated aluminum window frames, window walls, and door frames and which is required to meet the specifications of Architectural Aluminum Manufacturers Association AAMA 605.2-1980.
Camouflage	A coating applied as a topcoat on equipment to conceal such equipment from detection.
Cleanup Material	A VOC-containing material used to clean parts and application equipment used in miscellaneous metal parts and products coating operations.
Coating Remover (Stripper)	A material applied to the surface of any miscellaneous metal part or product to completely remove maskants, coatings or coating residues. A coating remover (stripper) is not a surface preparation material or cleanup material. Material used for the removal of overspray is not considered a coating remover.
Electrical Insulating	A coating which is applied to electrical components expressly for the purpose of electrical insulation.
Extreme High Gloss	A coating which, when tested by American Society for Testing Materials test method D-523 adopted in 1980, shows a 75% reflectance on a 60° meter.
Etching Filler	A coating which contains at least ½ percent acid by weight, as determined by the method specified in Section 502.2, and less than 23 percent solids by weight, as determined by the method specified in Section 502.7, and is used instead of applying a pretreatment wash primer followed by a primer.
Extreme Performance	A coating that is used on a metal surface where the coated surface, in its intended use, is acutely or chronically exposed to salt water, corrosives, caustics, acids, oxidizing agents, wind or ocean driven debris or electromagnetic pulse.
Heat Resistant	A coating used on a metal surface where the coated surface must withstand a temperature of at least 400°F during normal use.
Metallic/Iridescent	Any coating which contains more than 5.0 g/l (0.042 lb/gal) of metal or iridescent particles, as applied, where such particles are visible in the dried film.
Non-Skid	Any coating which has, as its primary purpose, the creation of traction to prevent slippage. (This definition will sunset on April 28, 2011).
Prefabricated Architectural Component	Prefabricated metal parts and products which are to be used as architectural appurtenances or structures and which are coated in a shop environment, not including window frames and door frames.
Pretreatment Wash Primer	A coating which contains at least ½ percent acid by weight, as determined in Section 502.2, and is applied directly to metal surfaces to provide surface etching and corrosion resistance or adhesion of subsequent coatings. A pretreatment wash primer is not a surface preparation material as defined in Section 242.
Silicone Release Coating	A coating which contains silicon resin and is intended to prevent a substance from sticking to metal surfaces such as baking pans.
Solar Absorbent	A coating which has, as its primary purpose, the absorption of solar radiation.
Surface Preparation Material	A VOC-containing material applied to the surface of any miscellaneous metal part or product prior to the application of coatings to clean the substrate or to promote adhesion of subsequent coatings.

SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT
RULE 451 – SURFACE COATING OF MISCELLANEOUS METAL PARTS & PRODUCTS
LIST OF CURRENTLY USED MATERIALS

P/O # _____

RULE 451 COATING CATEGORY PER SECTIONS 301, 303, 305 OR EXEMPT IN SECTION 110 <i>Refer to definitions</i>	MATERIAL TYPE (INDICATE MANUFACTURER, PRODUCT NAME & PRODUCT CODE)			MIXING RATIO AS APPLIED [A]	VOC CONTENT AS APPLIED EXCLUDING WATER AND EXEMPT COMPOUNDS g/l (lb/gal) [B]	VOC CONTENT AS APPLIED INCLUDING WATER AND EXEMPT COMPOUNDS g/l (lb/gal) [C]	MATERIAL EXCEEDING VOC LIMITS? (YES/NO) [D]
	MATERIAL	ADDITIVE	SOLVENT				
1.							
2.							
3.							
4.							
5.							
6.							
7.							
8.							

[A] Mixing ratio of coating, reducer, retarder, catalyst, hardener, additive, etc. as applied.

[B] Also known as **Coating VOC**. Used to demonstrate compliance with the VOC limits in Rule 451, Section 301.

[C] Also known as **Material VOC**. Used to demonstrate compliance with the VOC limits in Rule 451, Sections 303 & 305 and to calculate ROC emissions. Alternatively, Coating VOC may be used to calculate ROC emissions, but this calculation overestimates the actual emissions.

[D] VOC limits as specified in Rule 451, Sections 301, 303, 305.3 & 305.4, including materials under the “low usage” exemption.

For assistance with this form, please call the SMAQMD's Compliance Assistance Hotline at 279-207-1122 ext 99

SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT
RULE 451 – SURFACE COATING OF MISCELLANEOUS METAL PARTS & PRODUCTS
MONTHLY USAGE AND EMISSIONS RECORD OF MATERIALS COMPLYING
WITH THE VOC CONTENT LIMITS IN SECTIONS 301, 303, 305.3 & 305.4

MONTH _____ 20 _____ P/O # _____

RULE 451 COATING CATEGORY (SECTIONS 301, 303 & 305) <i>Refer to definitions</i>	METHOD OF APPLICATION (SECTION 304)	TOTAL APPLIED VOLUME gal/month [A]	VOC CONTENT AS APPLIED INCLUDING WATER & EXEMPT COMPOUNDS lb/gal [B]	MONTHLY ROC EMISSIONS lb/month [C]
SECTION 301				
ALUMINUM COATING FOR WINDOW FRAMES AND DOOR FRAMES				
CAMOUFLAGE				
ELECTRICAL INSULATING				
EXTREME HIGH GLOSS				
ETCHING FILLER				
EXTREME PERFORMANCE				
HEAT RESISTANT				
METALLIC/IRIDESCENT				
NON-SKID				
PREFABRICATED ARCHITECTURAL COMPONENT				
PRETREATMENT WASH PRIMER				
SILICONE RELEASE COATING				
SOLAR ABSORBENT				
ALL OTHER COATINGS				
SECTION 303				
COATING REMOVER (STRIPPER)				
SECTION 305.3				
CLEANUP SOLVENT FOR APPLICATION EQUIPMENT				
SECTION 305.5				
CLEANUP SOLVENT FOR SURFACE PREPARATION				
ROC EMISSIONS, lb/month				
ROC EMISSIONS, lb/quarter (TO-DATE)				

[A] Volume after mixing to include the coating, reducer, retarder, catalyst, hardener, additive, etc.
[B] Also known as Material VOC. Used to calculate ROC emissions.
[C] ROC Monthly Emissions = [A] x [B]. These are the total emissions from all types of coatings and solvents used. Quarterly ROC emissions are determined by adding the monthly emissions in each calendar quarter.

For assistance with this form, please call the SMAQMD's Compliance Assistance Hotline at 279-207-1122 ext 99

SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT
RULE 451 – SURFACE COATING OF MISCELLANEOUS METAL PARTS & PRODUCTS
QUARTERLY EMISSIONS SUMMARY

YEAR _____

P/O # _____

FIRST QUARTER	
MONTH	MONTHLY EMISSIONS [A] (May be obtained from FORM 451B)
January	
February	
March	
TOTAL QUARTERLY ROC EMISSIONS, LB/QUARTER	

SECOND QUARTER	
MONTH	MONTHLY EMISSIONS [A] (May be obtained from FORM 451B)
April	
May	
June	
TOTAL QUARTERLY ROC EMISSIONS, LB/QUARTER	

THIRD QUARTER	
MONTH	MONTHLY EMISSIONS [A] (May be obtained from FORM 451B)
July	
August	
September	
TOTAL QUARTERLY ROC EMISSIONS, LB/QUARTER	

FOURTH QUARTER	
MONTH	MONTHLY EMISSIONS [A] (May be obtained from FORM 451B)
October	
November	
December	
TOTAL QUARTERLY ROC EMISSIONS, LB/QUARTER	

[A] Monthly ROC emissions are the total emissions from all types of coatings and solvents used.

SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT
RULE 451 – SURFACE COATING OF MISCELLANEOUS METAL PARTS & PRODUCTS
MONTHLY USAGE FOR LOW USAGE (EXEMPTION) OF MATERIALS EXCEEDING
THE VOC CONTENT LIMITS IN SECTIONS 301, 303, 305.3 & 305.4

MONTH _____ 20 _____

P/O # _____

RULE 451 COATING CATEGORY (SECTIONS 301, 302 & 304) <i>Refer to definitions at the back</i>	MATERIAL TYPE (INDICATE MANUFACTURER, PRODUCT NAME & PRODUCT CODE)	TOTAL APPLIED VOLUME gal/month [A]	VOC CONTENT AS APPLIED INCLUDING WATER & EXEMPT COMPOUNDS lb/gal [B]	MONTHLY ROC EMISSIONS lb/month [C]
1.				
2.				
3.				
4.				
5.				
6.				
7.				
8.				
9.				
10.				
ROC EMISSIONS, lb/month				
ROC EMISSIONS, lb/quarter (TO-DATE)				

[A] Volume after mixing to include the coating, reducer, retarder, catalyst, hardener, additive, etc.

[B] Also known as Material VOC. Used to calculate ROC emissions.

[C] ROC Monthly Emissions = [A] x [B]. These are the total emissions from coatings and solvents used exceeding the VOC limits in Sections 301, 303, 305.3 & 305.4. Quarterly ROC emissions are determined by adding the monthly emissions in each calendar quarter.

Rule 451, Section 110 Low usage exemption of materials exceeding the VOC limits pursuant to Sections 301, 303, 305.3 & 305.4:

Max. Usage Limit

<55 gal/yr

For assistance with this form, please call the SMAQMD's Compliance Assistance Hotline at 279-207-1122 ext 99

**SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT
 RULE 451 – SURFACE COATING OF MISCELLANEOUS METAL PARTS & PRODUCTS
 DAILY USAGE RECORD OF NON-COMPLIANT MATERIALS**

YEAR _____

P/O # _____

DATE			MATERIAL TYPE (INDICATE MANUFACTURER, PRODUCT NAME & PRODUCT CODE)	VOC CONTENT AS APPLIED EXCLUDING WATER & EXEMPT COMPOUNDS lb/gal [A]	TOTAL APPLIED VOLUME gal/day [B]
MO	DAY	YR			

Note: NON-COMPLIANT MATERIAL is a coating or solvent that EXCEEDS THE VOC CONTENT LIMITS SPECIFIED IN RULE 451, SECTIONS 301, 303, 305.3 OR 305.4 AND THE USAGE IS IN EXCESS OF THE ALLOWABLE VOLUMES SPECIFIED IN SECTION 110.

- [A] Also know as **Coating VOC**. Used to demonstrate compliance with the VOC limits in Rule 451, Sections 301, 303, 305.3 & 305.4.
- [B] **SECTION 110:** Low usage exemption of materials exceeding the VOC limits pursuant to Sections 301, 303, 305.3 & 305.4.

Max. Usage Limit
 <55 gal/yr

SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT
RULE 451 – SURFACE COATING OF MISCELLANEOUS METAL PARTS & PRODUCTS
ANNUAL REPORT FOR LOW USAGE EXEMPTION
(MATERIALS EXCEEDING VOC CONTENT LIMITS)

Submit to the District by January 31st

YEAR _____

P/O # _____

MATERIAL TYPE (INDICATE MANUFACTURER, PRODUCT NAME & PRODUCT CODE)	VOC CONTENT AS APPLIED EXCLUDING WATER & EXEMPT COMPOUNDS lb/gal [A]	TOTAL APPLIED VOLUME gal/year [B]
1.		
2.		
3.		
4.		
5.		
6.		
7.		
8.		
9.		
10.		
11.		
12.		

[A] Also know as **Coating VOC**. Used to demonstrate compliance with the VOC limits in Rule 451, Sections 301, 303, 305.3 & 305.4.

[B] **SECTION 110**: Low usage exemption of materials exceeding the VOC limits pursuant to Sections 301, 303, 305.3 & 305.4.

Max. Usage Limit

<55 gal/yr

For assistance with this form, please call the SMAQMD's Compliance Assistance Hotline at 279-207-1122 ext 99