SMAQMD BACT CLEARINGHOUSE

CATEGORY:

SOIL REMEDIATION

BACT Size:

SMALL EMITTER (<10 LB/DAY) AND MIN

SOIL THERMAL DESORPTION

BACT Determination Number:

93

BACT Determination Date:

11/21/2014

Equipment Information

Permit Number:

N/A -- Generic BACT Determination

Equipment Description:

SOIL THERMAL DESORPTION

Unit Size/Rating/Capacity:

Low-temperature thermal desorption volitization

Equipment Location:

BACT Determination Information

ROCs	Standard:	95% control efficiency
	Technology Description:	Thermal or catalytic oxidizer
	Basis:	Achieved in Pactice
NOx	Standard:	
	Technology Description:	Low NOx burner and natural gas/LPG firing
	Basis:	Achieved in Pactice
SOx	Standard:	
	Technology Description:	Natural gas or propane fuel and good combustion practices
	Basis:	Achieved in Pactice
PM10	Standard:	
	Technology Description:	Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency)
	Basis:	Achieved in Pactice
PM2.5	Standard:	
1 1412.0	Technology Description:	Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency)
	Basis:	Achieved in Pactice
co	Standard:	
	Technology Description:	Natural gas or propane fuel and good combustion practices
	Basis:	Achieved in Pactice
LEAD	Standard:	
\	Technology	Natural gas or propane fuel and good combustion practices.
	Description: Basis:	Achieved in Pactice

Comments: PM10 and PM2.5: Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency)

District Contact: Michelle Joe

Phone No.: (916) 874 - 4853

email: mjoe@airquality.org



BEST AVAILABLE CONTROL TECHNOLOGY DETERMINATION

	DETERMINATION NO.:	93	
	DATE:	November 21, 2014	
	ENGINEER:	Michelle Joe	
Category/General Equip Description:	Soil Remediation		
Equipment Specific Description:	Soil Thermal Desorption		
Equipment Size/Rating:	Small Emitter (< 10 lb/day) and Minor Source BACT		
Previous BACT Det. No.:	None		

This BACT determination will create a new BACT determination for Soil Remediation - Soil Thermal Desorption. Thermal desorption (also known as low-temperature thermal volatilization, thermal stripping, and soil roasting) is an ex-situ remediation technology that uses heat to physically separate (volatilize and desorb) petroleum hydrocarbons from excavated soils.

BACT ANALYSIS

Step 1: Identify All Control Technologies

The following control technologies are currently employed as BACT for Soil Remediation -- Soil Thermal Desorption by the following BACT Clearinghouses:

BACT Clearinghouse	(A)	Best Available Control Technology (BACT)
SMAQMD	222	For VOC: A BACT standard has not been established.
EPA RBLC		For VOC: A BACT standard has not been established.
CARB		For VOC: A BACT standard has not been established.
South Coast AQMD		For VOC: A BACT standard has not been established.

BACT Clearinghouse	(A)	Best Available Control Technology (BACT)	
Bay Area AQMD	999	For VOC: A BACT standard has not been established.	
	AP	For VOC: Thermal or catalytic oxidization with 95% control efficiency.	
San Joaquin Valley APCD	AP	For NOx: Low NOx burner and natural gas/LPG firing.	
	AP	For PM10: Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency).	

⁽A) AP = Achieved in Practice, TF = Technologically Feasible

The following control technologies have been identified:

For VOC:

Thermal or catalytic oxidization with 95% control efficiency.

For NOx:

Low NOx burner and natural gas/LPG firing.

For SOx:

Natural gas or propane fuel and good combustion practices.

For PM10:

Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency).

For PM2.5:

Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency).

For CO:

Natural gas or propane fuel and good combustion practices.

For Lead:

Natural gas or propane fuel and good combustion practices.

Step 2: Eliminate Technologically Infeasible Options

All identified technologies are feasible.

⁽B) Emissions limit was not specified because a limit that applies to all equipment within the category is not possible. Refer to discussion (below).

BACT Determination Soil Remediation – Soil Thermal Desorption November 21, 2014 Page 3 of 3

Step 3: Rank Remaining Control Technologies by Control Effectiveness

The control technologies listed in Step 1 for VOC, NOx, SOx, PM10, PM2.5, CO, and Lead do not have any alternative technologies to rank against.

Step 4: Select BACT

BACT for Soil Remediation - Soil Thermal Desorption for the following pollutants are as follows:

For VOC:

Thermal or catalytic oxidization with 95% control efficiency.

For NOx:

Low NOx burner and natural gas/LPG firing.

For SOx:

Natural gas or propane fuel and good combustion practices.

For PM10:

Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency).

For PM2.5:

Fabric filter serving desorber exhaust (99% control efficiency) and soil covered or adequate moisture content such that visible emissions are less than 5% (90% control efficiency).

For CO:

Natural gas or propane fuel and good combustion practices.

For Lead:

Natural gas or propane fuel and good combustion practices.

REVIEWED BY:	Bin I Kul	DATE: _	12-1-14
APPROVED BY:	prye les grue	DATE: _	12-15-19